

# PRODUCT SPECIFICATION

REFERENCE NO: QAP / 03 / D4



**HAYCARB**  
Activated carbon solutions

## Haycarb Air Series

### Flue Gas Treatment

#### RIAF 1002 — STANDARD PRODUCT SPECIFICATION

| PARAMETER                       | VALUE    | TEST METHOD    |
|---------------------------------|----------|----------------|
| Iodine Number (mg/g) (Base)     | Min: 852 | ASTM           |
| Moisture (% wt/wt)              | Max: 10  | ASTM           |
| Ash (% wt)                      | Max: 6   | ASTM           |
| pH                              | 9-11     | ASTM           |
| Particles size 325 ASTM mesh    |          | HC (WET SIEVE) |
| > 325 mesh (0.045 mm) (% by wt) | Max: 10  |                |
| < 325 mesh (0.045 mm) (% by wt) | Min: 90  |                |

This product is also available in below particle sizes



Haycarb Activated Carbon grades that are Tested and Certified by NSF International against NSF/ANSI Standard 42 for material requirements only, are listed on: [www.nsf.org/certified/DWTU](http://www.nsf.org/certified/DWTU)

Component



ISO 9001:2008 Certified



ISO 14001:2004 Certified



[www.haycarb.com](http://www.haycarb.com)