



**HAYCARB**  
Activated carbon solutions

## Haycarb Air Series

### Military Applications

#### RPPM 3008 — STANDARD PRODUCT SPECIFICATION

PARAMETER	VALUE	TEST METHOD
Carbon Tetrachloride Adsorption (% by wt) (Base)	Min:	ASTM
Iodine Number (mg/g) (Base)	Min:	ASTM
Apparent Density (g/cc)	Min: 0.39	ASTM
Moisture (% wt/wt)	Max: 2.5	ASTM
Ash (% wt)	Max: 3.5	ASTM
pH		ASTM
Hardness No	Min:	ASTM
Particles size 6x16 ASTM mesh		
> 6 mesh ( 3.35 mm ) (% by wt)	Max: 5	ASTM
6X16 mesh (3.35 mm x 1.18 mm) (% by wt)	Min: 90	ASTM
< 16 mesh (1.18 mm ) (% by wt)	Max: 5	ASTM

This product is also available in below particle sizes



Haycarb Activated Carbon grades that are Tested and Certified by NSF International against NSF/ANSI Standard 42 for material requirements only, are listed on: [www.nsf.org/certified/DWTU](http://www.nsf.org/certified/DWTU)  
Component



ISO 9001:2008 Certified



ISO 14001:2004 Certified



[www.haycarb.com](http://www.haycarb.com)