

PRODUCT SPECIFICATION

REFERENCE NO: QAP / 03 / D4



HAYCARB
Activated carbon solutions

Haycarb Water Series

Filter Cartridges and Carbon Blocks

RWAP 2021 — STANDARD PRODUCT SPECIFICATION

| PARAMETER | VALUE | TEST METHOD |
|--|-----------|-------------|
| Carbon Tetrachloride Adsorption (% by wt) | Min: 50 | ASTM |
| Iodine Number (mg/g) | Min: 1050 | ASTM |
| Apparent Density (g/cc) | Min: 0.48 | ASTM |
| Moisture (% wt/wt) | Max: 5 | ASTM |
| Ash (% wt) | Max: 3 | ASTM |
| pH | 8-10 | ASTM |
| Hardness No | Min: 98 | ASTM |
| Particles size 14x45 US mesh | | ASTM |
| > 14 mesh (1.40 mm) (% wt/wt) | Max: 5 | |
| 14x45 mesh (1.40 mmx 0.355 mm) (% wt/wt) | Min: 90 | |
| < 45 mesh (0.355 mm) (% wt/wt) | Max: 5 | |



Haycarb Activated Carbon grades that are Tested and Certified by NSF International against NSF/ANSI Standard 42 for material requirements only, are listed on: www.nsf.org/certified/DWTU

Component



ISO 9001:2008 Certified



ISO 14001:2004 Certified



www.haycarb.com