

PRODUCT SPECIFICATION

REFERENCE NO: QAP / 03 / D4



HAYCARB
Activated carbon solutions

Haycarb Water Series

Filter Cartridges and Carbon Blocks

RWAP 4001 — STANDARD PRODUCT SPECIFICATION

PARAMETER	VALUE	TEST METHOD
Carbon Tetrachloride Adsorption (% by wt)	Min: 50	ASTM
Iodine Number (mg/g)	Min: 1050	ASTM
Apparent Density (g/cc)	Min: 0.44	ASTM
Moisture (% wt/wt)	Max: 5	ASTM
Ash (% wt)	Max: 5	ASTM
pH	8-11	ASTM
Particles size 80x325 US mesh		
> 80 mesh (0.180 mm) (% by wt)	Max: 17	LASER
80X325 mesh (0.180 mm x 0.045 mm) (% by wt)	Test & Report	LASER
< 325 mesh (0.045mm) (% by wt)	Max: 7-15	LASER
Mean Particle Diameter (µm)	90-120	LASER

This product is also available in below particle sizes



Haycarb Activated Carbon grades that are Tested and Certified by NSF International against NSF/ANSI Standard 42 for material requirements only, are listed on: www.nsf.org/certified/DWTU

Component



ISO 9001:2008 Certified



ISO 14001:2004 Certified



www.haycarb.com